



## Gulf Formula GX 5W-40 Passenger Car Motor Oil

### Product Description

**Gulf Formula GX 5W-40** is the most advanced high performance synthetic passenger car motor oils exclusively developed for latest generation passenger cars and light duty vehicles. The latest formulation technology used in this oil provides unmatched levels of overall lubrication for all types of vehicles, especially high output, turbocharged, supercharged multi valve fuel injected engines in passenger cars, SUVs, light vans & trucks. It is specially designed to ensure maximum protection over extended oil-change intervals. It exceeds the requirements of virtually all the major global OEMs and industry standards.

### Features & Benefits

- Outstanding thermo-oxidative stability reduces deposits & sludge build-up and facilitates extended drain intervals & engine life
- Superior antiwear technology provides exceptional wear protection under all conditions
- Excellent low volatility characteristics reduce oil consumption & hydro-carbon pollution
- Active cleaning agents ensure maximum engine cleanliness
- Enhanced frictional properties result in fuel savings
- Excellent low temperature properties lead to quick cold start and ensure wear protection at start-up

### Applications

- Recommended for all latest, high performance gasoline and diesel engines in cars, SUVs, light vans & trucks, particularly those using recent technologies (multi-valve engines, turbo compressors, and high cylinder capacity) and the new direct injection diesel engines with or without common rail
- Especially suited to city stop-and-go, heavy load and/or high-speed applications where the conventional oils fail to perform and where such quality oils are recommended

### Specifications, Approvals & Typical Properties

Meets the following Specifications		5W-40
ACEA A3/B4		X
API SN / SM / SL,		X
BMW Longlife-01		X
Chrysler MS 10902 (ACEA A3/B4)		X
Porsche A40		X
Recommendation		
Fiat 9.55535-Z2		X
Has the following Approvals		
MB-Approval 229.5,		X
VW 502 00, 505 00		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	14.2
Viscosity Index	D 2270	168
Flash Point, °C	D 92	230
Pour Point, °C	D 97	-36
TBN, mg KOH/g	D 2896	10.5
Density @ 15°C, Kg/l	D 1298	0.8573
Sulphated Ash, %wt	D 874	1.29

2020/10

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Teklub Canada Ltd Official Distributor of Gulf Oil International in Canada

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information of the suitability of the products. Teklub Canada Ltd reserves the right to modify and change its products and specifications without prior notice.

[www.gulfoil.ca](http://www.gulfoil.ca)